



KBV-P 气动球阀

KL Hygienic Ball Valves

- 工作压力 0-10bar
- 工作范围 -40~150°C(标准), -40~120°C(全包)
- 驱动机构 气动控制
最大气源压力
工作温度:-20~80°C
- 密封材质 PTFE
- 阀体设计 直通阀体
- 阀体材质 316L (EN1.4409 CF3M)
- 接口尺寸 DN15-DN100
- 接口方式 焊式 / 卡式
- 表面处理 外表面 Ra≤0.5 μm, 内表面 Ra≤0.8 μm
- 符合标准 常关 (NC), 常开 (NO), 气/气 (A/A)
- 接口标准 ISO, ASME BPE, 3A



KBV-P (NC): 卡式气动蝶阀 (标准)

No.	SIZE	A	B	L	H
1507401-000050	15	25.0	9.4	88.6	165
1507401-000075	20	25.0	15.8	102.7	165
1207401-000025	25	50.5	22.6	115.2	170
1207401-000038	38	50.5	35.6	139.9	200
1207401-000051	51	64.0	48.6	158.1	220
1507401-000250	63	77.5	60.3	198.2	250
1507401-000300	76	91.0	72.9	227.5	275
1507401-000400	101	119.0	97.6	242.0	315


KBV-P (NC): 卡式气动蝶阀 (全包)

No.	SIZE	A	B	L	H
1507402-000050	15	25.0	9.4	88.6	165
1507402-000075	20	25.0	15.8	102.7	165
1207402-000025	25	50.5	22.6	115.2	170
1207402-000038	38	50.5	35.6	139.9	200
1207402-000051	51	64.0	48.6	158.1	220
1507402-000250	63	77.5	60.3	198.2	250
1507402-000300	76	91.0	72.9	227.5	275
1507402-000400	101	119.0	97.6	242.0	315



KBV-P (NC): 卡式气动球阀 (标准 带反馈信号的)

No.	SIZE	A	B	L	H
1507405-000050	15	25.0	9.4	88.6	165
1507405-000075	20	25.0	15.8	102.7	165
1507405-000025	25	50.5	22.6	115.2	170
1207404-000038	38	50.5	35.6	139.9	200
1207404-000051	51	64.0	48.6	158.1	220
1207404-000250	63	77.5	60.3	198.2	250
1507405-000300	76	91.0	72.9	227.5	275
1507405-000400	101	119.0	97.6	242.0	315



KBV-P (A/A): 卡式气动球阀 (全包 带反馈信号的)

No.	SIZE	A	B	L	H
1507403-000050	15	25.0	10.3	88.6	165
1507403-000075	20	25.0	16.7	102.7	165
1207403-000025	25	50.5	22.6	115.2	170
1207403-000038	38	50.5	35.6	139.9	200
1207403-000051	51	64.0	48.6	158.1	220
1507403-000250	63	77.5	60.3	198.2	250
1507403-000300	76	91.0	72.9	227.5	275
1507403-000400	101	119.0	97.6	242.0	315

