

AGRASTAR SD /16

TUBI ASPIRAZIONE E MANDATA IN FEP PER COSMETICA E FARMACEUTICA
 SUCTION AND DELIVERY FEP HOSE FDA FOR COSMETIC AND PHARMA INDUSTRY
 TUYAU ASPIRATION ET REFOULEMENT EN FEP DANS LA COSMETIQUE ET PHARMACEUTIQUE
 FEP SAUG-UND DRUCKSCHLAUCH FÜR KOSMETICA UND PHARMAEZEUGNIS



🇮🇹 APPLICAZIONE	🇬🇧 APPLICATION	🇫🇷 APPLICATION	🇩🇪 ANWENDUNG
Aspirazione e mandata di prodotti farmaceutici, cosmetici ed alimentari, altissima temperatura	Suction and delivery hose for pharmaceutical, cosmetic and food stuffs, very high temperature	Tuyau aspiration et refolement des produits pharmaceutiques, cosmétiques et alimentaires, température très élevée	Hochwertiger Saug- und Druckschlauch, für Arzneimittel, Kosmetika und Lebensmittel, hochtemperaturbeständig
SOTTOSTRATO	TUBE	TUBE INTERIEUR	INNENSEELE
Bianco, liscio, lucido, in FEP (Etilene Propilene fluorinato), non conduttivo	White, glossy, non conductive FEP (Fluorinate Ethylene Propylene)	Blanche, poli, FEP (éthylène-propylène fluoré), pas conductive	Weiß, glänzend, nicht-leitend FEP (Fluorinated Ethylene Propylene)
RINFORZO	REINFORCEMENT	ARMATURE	EINLAGEN
Tessuti sintetici ad alta tenacità, con spirali metalliche incorporate e 2 cord in rame per la messa a terra della tubazione	High strength synthetic plies, with steel spirals and 2 crossing copper wires for hose grounding	Nappes synthétiques très résistantes avec spirales métalliques et 2 fils en cuivre de masse	Hochreißfestes synthetisches Cordgewebe mit eingearbeiteter Stahldrahtspirale und 2 antistatischen Kupferlitzen zur Erdung
COPERTURA	COVER	REVETEMENT EXTERIEUR	DECKE
Blu, liscia ad impressione tela in gomma EPDM , resistente all'abrasione, all'ozono e agli agenti atmosferici	Blue, smooth, cloth impression EPDM rubber, resistant to abrasion, ozone and weather	EPDM bleu, lisse, grain toile, résistant à l'abrasion, à l'ozone et aux agents atmosphériques	Blau, stoffgemustert, EPDM -Qualität, abrieb-, ozon- und witterungsbeständig
NORME	SPECIFICATIONS	NORMES	NORMEN
FDA titolo 21 art.177.2600 (f) per alimenti grassi, BfR, ADI free, D.M. 21/03/73, CE1935/2004, PHTHALATE free Conformity to USP XXXVI NF31 ed.2013 <87> and <88> class VI and other normative references	FDA title 21 art.177.2600 (f) for fatty foods, BfR, ADI free, D.M. 21/03/73, CE1935/2004, PHTHALATE free Conformity to USP XXXVI NF31 ed.2013 <87> and <88> class VI and other normative references	FDA titre 21 et article 177.2666 (f) pour aliments gras, BfR et ADI free, D.M.21/03/73, CE1935/2004, PHTHALATE free Conformity to USP XXXVI NF31 ed.2013 <87> and <88> class VI and other normative references	FDA Titel 21 Art. 177.2600 (f) für fetthaltige Lebensmittel, BfR, ADI frei, D.M. 21/03/73, CE1935/2004, PHTHALATE frei Conformity to USP XXXVI NF31 ed.2013 <87> and <88> class VI and other normative references
TEMPERATURA D'ESERCIZIO	WORKING TEMPERATURE	TEMPERATURE	BETRIEBSTEMPERATUR
-50°C +170°C	-58°F + 338°F	-50°C +170°C	-50°C +170°C

											
ID	OD	WEIGHT	WP	BP	BENDING RADIUS	VACUUM	COIL LENGTH				
mm	inch	kg/m	bar	psi	mm	bar	m				
19	3/4	0,71	16	240	125	0,9	20				
25	1	0,87	16	240	150	0,9	20				
32	1 1/4	1,07	16	240	175	0,9	20				
38	1 1/2	1,35	16	240	225	0,9	20				
51	2	2,29	16	240	275	0,9	20				
63,5	2 1/2	2,51	16	240	300	0,9	20				
76	3	3,08	16	240	350	0,9	20				

